


## **CARBON DIOXIDE**

Usha Plus CO<sub>2</sub> GAS extinguishers are characterized by their high performance for fires involving electrical risk like computers, office equipment, generators etc. CO2 is non conductive, clean and safe, ensuring minimal damage to electrical equipment and furnishings.




















- → CE Marked Extinguishers
- → High quality epoxy enamel paint
- Controlled discharge
- → Brass head valve with simple squeeze operations provided with pressure relief disc.
- → Manganese steel (IS 7285)
- → Easy & more economical to maintain & service
- Swivel hom with no freeze burn, with greater directional control of CO2 discharge through hom rotation feature.
- → International Color Coding Operation Sticker



MODEL	UFC 2	UFC 3	UFC 4.5
Capacity	2Kg	3Kg	4.5Kg
Fire Rating	8B	13B	21B
Average Discharge Time	12 sec	14 sec	14 sec
Height (Approx.)	580 mm	545 mm	700 mm
Diameter (Approx.)	108 <u>+</u> 10mm	140 <u>+</u> 10mm	140 <u>+</u> 10mm
Filled weight (Approx.)	8.9Kg or 8.2kg	12.5Kg or11.4kg	17Kg or 16.4kg
Empty (Approx.)	6.9Kg or 6.2kg	9.5 Kg or 8.4kg	12.5Kgor11.9kg
Operating Temperature	-30 C to +55 C	-30 C to +55 C	-30 C to +55 C
Maximum Service Pressure	106bar	110bar	105bar
Test Pressure	250 bar/cm²	250 bar/cm²	250 bar/cm²

## \*Top wheel Default model



## (Optional Accessories)

\*Extinguisher Floor Stand



## www.ushafire.com